

3430.** RING TERMINALS · WITH INSULATION SUPPORT



Specification 10.5 mm Plate

Ø (mm) 4,3

Wire size mm² (AWG) 0,2-0,5 (24-20)

Ø Insulation (mm) 1,2-2,1

Materials, temperature and contact resistance

| Part nr. | Material | Finishing | Max. Temp. (°C) |
|----------|----------|------------|-----------------|
| 3430.02 | Brass | Tin plated | 120 |

Material thickness (mm) 0,6

Max. rated current

| Wire section | 3430.02 |
|----------------------|---------|
| 0.50 mm ² | 6A |

Application tool MN3430

Wire strip length 5.2 (±0.3) mm

Crimping parameters & pull out force

| Wire section (±10%) | Conductor | | Insulator | Pull-out force (N) |
|----------------------|--------------|--------------|--------------|--------------------|
| | Height (mm) | Width (mm) | Width (mm) | |
| 0.25 mm ² | 1.55 (±0.03) | 2.85 (±0.10) | 3.25 (±0.10) | 28N @ 60s |
| 0.35 mm ² | 1.60 (±0.03) | 2.86 (±0.10) | 3.25 (±0.10) | 40N @ 60s |
| 0.50 mm ² | 1.65 (±0.03) | 2.87 (±0.10) | 3.25 (±0.10) | 56N @ 60s |



Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Winding number 6000

Approvals



Drawing



3430.**
RING TERMINALS · WITH INSULATION SUPPORT**Disclaimer**

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

| Rev. Nr. | Concept | Date | Created/Revised | Approved |
|----------|--|------------|-----------------------------|------------------------------|
| A1 | Datasheet generated automatically [A1] | 2024-06-11 | E. Roura (Laboratory dept.) | D. Yabar (Engineering dept.) |

Escubedo Connection Systems, S.A.U. · Ctra. de Girona-Olot Km. 35,5 · 17843 Riudellots de la Creu · Girona · Spain
Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com