



4832.**
6.3 (.250) TYPE SERIES · RECEPTACLES



Specification Low insertion

For male (mm) 6,3x0,8

Wire size mm² (AWG) 1-2,5 (18-14)

Ø Insulation (mm) 3-4,3

Materials, temperature and contact resistance

Part nr.	Material	Finishing	Max. Temp. (°C)	Contact Resist (mΩ)
4832.00	Brass	Natural	110	0.80
4832.01	Brass	Pre-tin-plated	120	0.60
4832.02	Brass	Tin plated	120	0.65
4832.24	Steel	Nickel-plated	300	2.50
4832.30	Bronze	Natural	120	1.00
4832.31	Bronze	Pre-tin-plated	130	0.70
4832.32	Bronze	Tin plated	130	0.75
4832.70	German Silver	Natural	210	3.00

Material thickness (mm) 0,4

Max. rated current

Wire section	4832.00 / 01 / 02 / 24 / 30 / 31 / 32 / 70
1.00 mm ²	12A
1.50 mm ²	16A
2.50 mm ²	20A

Insertion / Withdrawal forces


	4832.00 / 30 / 70	4832.01 / 02 / 24 / 31 / 32
1st Insertion (max)	35N ¹	35N ¹
1st Withdrawal (max)	60N ¹	60N ¹
1st Withdrawal (min)	27N ¹	22N ¹
6th Withdrawal (min)	22N ¹	18N ¹

¹ Valid for Natural Brass Tab

Application tool MN4832

Wire strip length 5.5 (±0.5) mm

Crimping parameters & pull out force

Wire section (±10%)	Conductor 		Insulator Width (mm)	Pull-out force (N)
	Height (mm)	Width (mm)		
1.00 mm ²	1.55 (±0.05)	3.05 (±0.05)	4.09 (±0.10)	108N @ 60s
1.50 mm ²	1.70 (±0.05)	3.06 (±0.05)	4.10 (±0.10)	150N @ 60s
2.00 mm ²	1.80 (±0.05)	3.07 (±0.05)	4.11 (±0.10)	150N @ 60s
2.50 mm ²	1.90 (±0.05)	3.08 (±0.05)	4.12 (±0.10)	230N @ 60s
14 AWG	1.80	3.08	(T.B.D.)	223N @ 60s

Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Winding number 7000

Compatible connectors 26314**



4832.**

6.3 (.250) TYPE SERIES · RECEPTACLES





Approved regulations

Part nr.	Approval	Standard	File	Certified framework
4832.00	UL	UL 310	E211727	AWG 18-14 (16-41 Stranded Cu) / MN4832
4832.01	UL	UL 310	E211727	AWG 18-14 (16-41 Stranded Cu) / MN4832
4832.01	VDE	EN 61210	5000955-1433-0001 / 17165 / F310 / GRE	1,0 ... 2,5mm ² . 120°C max
4832.24	UL	UL 310	E211727	AWG 18-18 (16-16 Stranded Cu) / MN4832
4832.24	VDE	EN 61210	5000955-1433-0001 / 17166 / F310 / GRE	1,0 ... 2,5mm ² . 200°C max
4832.31	UL	UL 310	E211727	AWG 18-14 (16-41 Stranded Cu) / MN4832

Approvals



Drawing



Secc. Z-Z







4832.00 NATURAL BRASS
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried




Valid for Natural Brass Tab




4832.01 PRE-TIN-PLATED BRASS
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried




Valid for Natural Brass Tab




4832.02 TIN PLATED BRASS
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried




Valid for Natural Brass Tab




4832.24 NICKEL-PLATED STEEL
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried




Valid for Natural Brass Tab




4832.31 PRE-TIN-PLATED BRONZE
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried




Valid for Natural Brass Tab




4832.70 NATURAL GERMAN SILVER
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried



Valid for Natural Brass Tab



4832.**

6.3 (.250) TYPE SERIES · RECEPTACLES



(T.B.D.): To be determined

Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A3	Update Insertion / Withdrawal forces	2019-12-11	Laboratory Dept.	E. Roura
A2	Update de-rating curves	2018-11-08	Laboratory Dept.	E. Roura
A1	Datasheet generated automatically [A1]	2018-08-06	Laboratory Dep.t	E. Roura