

4842.** 6.3 (.250) TYPE SERIES · RECEPTACLES



Specification Low insertion based on standard design

Typology Short Terminal

For male (mm) 6,3x0,8

Wire size mm² (AWG) 1-2,5 (18-14)

Ø Insulation (mm) 3-4,3

Materials, temperature and contact resistance

Part nr.	Material	Finishing	Max. Temp. (°C)	Contact Resist (mΩ)
4842.00	Brass	Natural	110	0.50
4842.02	Brass	Tin plated	120	0.50
4842.30	Bronze	Natural	120	(T.B.D.)
4842.32	Bronze	Tin plated	130	(T.B.D.)
4842.70	German Silver	Natural	210	1.25

Material thickness (mm) 0,4

Max. rated current

Wire section	4842.00 / 02 / 30 / 32 / 70
1.00 mm ²	12A
1.50 mm ²	16A
2.50 mm ²	20A

Insertion / Withdrawal forces


	4842.00 / 30 / 70	4842.02 / 32
1st Insertion (max)	35N ¹	35N ¹
1st Withdrawal (min)	35N ¹	35N ¹
6th Withdrawal (min)	22N ¹	18N ¹

¹ Valid for Natural Brass Tab

Application tool MN4842

Wire strip length 5.0 (±0.5) mm

Crimping parameters & pull out force

Wire section (±10%)	Conductor 		Insulator	Pull-out force (N)
	Height (mm)	Width (mm)		
1.00 mm ²	1.60 (±0.05)	2.86 (±0.05)	4.20 (±0.10)	108N @ 60s
1.50 mm ²	1.75 (±0.05)	2.87 (±0.05)	4.21 (±0.10)	150N @ 60s
2.50 mm ²	2.05 (±0.05)	2.89 (±0.05)	4.22 (±0.10)	230N @ 60s

Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Winding number 8000

Compatible connectors 26310**, 26313**, 26316**, 26320**, 26321**



Approvals




4842.**
6.3 (.250) TYPE SERIES · RECEPTACLES



Drawing




Secc. Z-Z




4842.00 NATURAL BRASS
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried




Valid for Natural Brass Tab


4842.02 TIN PLATED BRASS
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried




Valid for Natural Brass Tab


4842.70 NATURAL GERMAN SILVER
6.3 (.250) TYPE SERIES · RECEPTACLES



Derating curve Current carrying capacity vs. Ambient temperature



Temperature rise curve Terminal temperature rise due to the current carried



Valid for Natural Brass Tab

4842.**
6.3 (.250) TYPE SERIES · RECEPTACLES


(T.B.D.): To be determined

Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A4	Change company name and logo	2021-10-21	E.Roura (laboratory dept.)	M.Codina (engineering dept.)
A3	Withdrawal forces updated	2021-02-23	E.Roura (laboratory dept.)	M.Codina (engineering dept.)
A2	Update 'Insertion / Withdrawal forces' note	2019-05-29	Laboratory Dept.	E. Roura
A1	Datasheet generated automatically [A1]	2018-07-23	Laboratory Dept.	E. Roura

Escubedo Connection Systems, S.A.U. · Ctra. de Girona-Olot Km. 35,5 · 17843 Riudellots de la Creu · Girona · Spain
 Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com