

# **PRODUCT DATASHEET**



### R5655\*\*-K RAST 5 TERMINALS AND CONNECTORS - MALE CONNECTORS

Specification

RAST 5 Crimp Connect Panel male connectors

#### **Thermal Characteristics**

Part nr.	Raw material	Color	Flammability Class (UL 94)	Glow Wire Test (GWT) (IEC60695-2-11)	Glow Wire Flammability Index (IEC60695-2-12)	RTI electrical (Max. Operating Temp.)
R565510-K	PA66V2	Natural	V2	(T.B.D.)	850ºC	105ºC
R565530-K	PA66V0	Natural	V0	(T.B.D.)	960ºC	140ºC
R565540-K	NO FLAME	Natural	V2	750ºC	960ºC	130ºC
R565570-K	PPV2 NF	Natural	V2	(T.B.D.)	(T.B.D.)	(T.B.D.)

For other materials and colors ask to: info@escubedo.com

### Compatible terminals


6421.\*\*, 6423.\*\*, 6424.\*\*, 6425.\*\*, 6426.\*\*, 6427.\*\*, 6432.\*\*, 6434.\*\*, 6438.\*\*, 6440.\*\*

## Insertion / Withdrawal forces

	R565510-K / 30 / 40 / 70
Terminal into connector cavity. Insertion force (max)	10N <sup>1</sup>
Terminal from connector cavity - only primary lock. Withdrawal force (min)	70N <sup>1</sup>

<sup>1</sup> Valid for compatible terminals

#### Drawing



(T.B.D.): To be determined

#### Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved				
A2	Change company name and logo	2021-10-21	E. Roura (Laboratory Dept.)	M. Codina (Engineering Dept.)				
A1	Datasheet generated automatically [A1]	2021-05-28	E. Roura (Laboratory Dept.)	M. Codina (Engineering Dept.)				
Escubedo Connection Systems, S.A.U. · Ctra. de Girona-Olot Km. 35,5 · 17843 Riudellots de la Creu · Girona · Spain Tel.: 34 972 171 706 · Fax: +34 972 171 714 · <u>info@escubedo.com</u> · <u>www.escubedo.com</u>								