

## 26313\*\*



### 6.3 MM (.250) UP STA / UP TBI 1 WAY RECEPTACLES HOUSING

**Description** Special Housing for 6.3 series UP STA / UP TBI

**Thermal characteristics**

Part Number	Raw Material	Flammability Class (UL 94)	Glow Wire Flammability Index (IEC60695-2-12)	RTI Electrical (Max. Operating Temp.)
263131*	PA66	V2	850°C	65 °C
263133*	PA68	V0	960°C	140 °C
263134*	PA	NF	960°C	65 °C

\* Colour

**Compatibility (Terminals supported)**


Wire size [mm <sup>2</sup> ]	PN. 6.3 STA	PN. 6.3 TBI
0.2 – 0.6	4420F**/4541.**	-
0.3 – 0.6	4622.**	-
0.5 – 1.0	4420.**/4540.**/4424.**/4626.**/4520.**/4548.	4820.**/4840.**
0.5 – 1.5	4646.**	-
1.0 – 2.5	4422***/4542.**/4648.**/4521.**	4822.**/4842.**
2.5 – 6.0	4425.**	4824.**
2.5 – 5.0	4544.**	4844.**

**Mechanical properties (Terminal-connector for way)**

1 <sup>st</sup> Insertion	7 N Max.
1 <sup>st</sup> Withdrawal	70 N Min.

**Drawing**

**Approvals**



**Disclaimer**

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicized only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us.

Rev. Nr.	Concept	Date	Created/Revised	Approved
1	Creation	21/10/2015	D.Martinez / E.Roura	Joan Carles Sanchez