

## 8805F\*\*



### SPECIAL TERMINALS – LAMPHOLDER - LAMP CONTACT

**Description** Lamp holder terminal for PS21W bulb. Lamp contact

**Wire section range** 0.50 mm<sup>2</sup> (AWG 20)

**Insulator Ø** 1.50 mm



Materials, Temperature	Part nr.	Material	Finishing	Max. Temp. (C°)
	8805F61	Inox	Pre-tin-plated	300

**Material thickness** 0.3 mm

Max. Rated current	Wire section (mm <sup>2</sup> )	Current (A)
	0.50	8

**Application tool** MN8805F


**Wire striping length** 4.00 (±0.5) mm


Crimping parameters & Pull out force	Wire section (mm <sup>2</sup> ±10%)	Conductor (mm) 		Insulator (mm) 		Pull-out force (N)
		Height (±0.05)	Width (measured)	Height (measured)	Width (measured)	
	0.50	1.20	1.85	1.95	2.40	>80

Note: Values only valid for the application tool specified.

**Packaging** 4500 Pieces on 25 mm cardboard reel, 12.5 mm terminal chain pitch

**Drawing**



<b>Approvals</b>	RoHS Compliant	
------------------	----------------	---

**Connectors Compatibility** [info@escubedo.com](mailto:info@escubedo.com)

**Disclaimer**

Data obtained from Escubedo Laboratory essays, using own methodology, cabling, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us.

Rev. Nr.	Modification	Date	Created/Revised	Approved
3	Update	11/07/2017	D.Martinez / E.Roura	X.Menac
2	Update	03/04/2017	D.Martinez / E.Roura	X.Menac
1	Creation	10/10/2013	D.Martinez	JC Sanchez